

## CADENAS DE CAUCHO

## RUBBER TRACKS

## GUMMIKETTEN



CONVENTIONAL				
	Innerguide Width	Outerguide Width	Profile	Roller Type
	23 mm	60 mm	B	2
Width x pitch x N° of links	180x60x30 / 180x60x34 / 180x60x37 180x60x38 / 180x60x40			
	23 mm	64 mm	L	1
Width x pitch x N° of links	180x72x33 / 180x72x34 / 180x72x36 180x72x37 / 180x72x38			
	23 mm	78 mm	C	1.2
Width x pitch x N° of links	200x72x33 / 200x72x34 / 200x72x35 200x72x38 / 200x72x39 / 200x72x40 200x72x41 / 200x72x42 / 200x72x45			
	23 mm	76 mm	R	2
Width x pitch x N° of links	230x72x39 / 230x72x42 / 230x72x43 230x72x44 / 230x72x45 / 230x72x46 230x72x47 / 230x72x48 / 230x72x50			
	23 mm	76 mm	H	2
Width x pitch x N° of links	250x72x42 / 250x72x43 / 250x72x44 250x72x45 / 250x72x46 / 250x72x47 250x72x48 / 250x72x49 / 250x72x50 250x72x51 / 250x72x52 / 250x72x57 250x72x64			
	40 mm	80 mm	S, H	2
Width x pitch x N° of links	320x100x38 / 320x100x39 / 320x100x40 320x100x41 / 320x100x42 / 320x100x43 320x100x44 / 320x100x45 / 320x100x46 320x100x47 / 320x100x48 / 320x100x49 320x100x50 / 320x100x51 / 320x100x52 320x100x53 / 320x100x54 / 320x100x55			

- » Todas las marcas
- » Máxima disponibilidad
- » Gran adherencia, gracias a una gran superficie de contacto con el suelo
- » Cableadas interiormente de acero

- » All brands
- » Maximum availability
- » High adhesion thanks to the large contact surface with the ground
- » Steel internal cabling

SHORT PITCH (I/C)				
	Innerguide Width	Outerguide Width	Profile	Roller Type
	30 mm	82 mm	M	3
Width x pitch x N° of links	300x52,5x70 / 300x52,5x72 300x52,5x74 / 300x52,5x76 300x52,5x78 / 300x52,5x80 300x52,5x82			
	40 mm	90 mm	W	3
Width x pitch x N° of links	300x55x70 / 300x55x72 / 300x55x74 300x55x76 / 300x55x78 / 300x55x80 300x55x82 / 300x55x84			
	52 mm	112 mm	W	3.4
Width x pitch x N° of links	400x73x70 / 400x73x72 / 400x73x74 400x73x76			
	56 mm	136 mm	T	3.4
Width x pitch x N° of links	400x81x70 / 400x81x72 / 400x81x74 400x81x76			

INTERCHANGEABLE				
	Innerguide Width	Outerguide Width	Profile	Roller Type
	25 mm	70 mm	R	3
Width x pitch x N° of links	230x96x30 / 230x96x31 / 230x96x32 230x96x33 / 230x96x34 / 230x96x35			
	40 mm	90 mm	A	4
Width x pitch x N° of links	300x109x35 / 300x109x36 / 300x109x37 300x109x38 / 300x109x39 / 300x109x40 300x109x41 / 300x109x42			
	31 mm	78 mm	P	3.4
Width x pitch x N° of links	300x109x35 N / 300x109x36 N 300x109x37 N / 300x109x38 N 300x109x39 N / 300x109x40 N 300x109x41 N / 300x109x42 N			
	52 mm	112 mm	R	3
Width x pitch x N° of links	400x146x35 / 400x146x36 400x146x37 / 400x146x38			

**SOLIS**<sup>®</sup>  
INDUSTRIAS DEL CAUCHO

AVDA. MANUEL SIRGO, 227 TREMAÑES - 33211 - GIJÓN, ASTURIAS - ESPAÑA

T: (+34) 985 32 00 55 / (+34) 985 31 40 02 F: (+34) 985 32 01 35

APARTADO 8126 - C.P. 33210 GIJÓN

solis@solis-sl.com

www.solis-sl.com